

**Treatability Results Available Using Chemical Remediation Systems  
(Treated, Removed and Landfilled)\***

Waste Type Source	TCLP Leachable Lead		TCLP Leachable Cadmium		Treatment Amount
	Before	After	Before	After	
<b>Soil</b> – Battery Site	267	<0.6			4%
<b>Incinerator</b> – Medical Waste	11.4	<0.6	(zinc) 12.9	<0.15	10%
<b>Landfill</b> – Brass Foundry	160	<0.2			10%
<b>Leaded Paint</b> – Steel Bridge	10.8	<0.6	0.15	<0.15	5%
<b>Sand</b> – Brass Foundry	42	<0.6	0.24	<0.15	10%
<b>Sludge</b> – Iron Foundry	8.1	<0.6	0.21	<0.15	1%
<b>Soil</b> – Apple Orchard	370	<0.2			10%
<b>K061</b> – Steel Mill	66	<0.6	8.7	<0.15	10%
<b>River Bottom</b> – Bridge Site	9	<0.6			1%
<b>Waste</b> – Aluminum Recycler	68	<0.1	0.25	.049	5%
<b>Baghouse Dust</b> – Grey Iron Foundry	11	<0.1	2.4	<0.005	7.5%
<b>Baghouse Dust</b> – Brass Foundry	260	<0.1	0.59	<0.005	10%
<b>Baghouse Dust</b> – Ductile Iron Foundry	31	<0.1	2.5	<0.005	10%

\*1994 Publication by prominent U.S. Manufacturer / Minerals Processor.  
\*Comparable to chemical treatment and additives before Metcap™ Patented Remediation Service, 1994

**J. Norman Stark, Chairman and CEO**  
[normstark@metlcap.com](mailto:normstark@metlcap.com)

**Brian D. Stark, Vice President**  
[brian@metlcap.com](mailto:brian@metlcap.com)

**Paul J. Stark**  
[parul@metlcap.com](mailto:parul@metlcap.com)

**The Stark Building** 1310 East 49th Street Cleveland, OH 44114 T: (216) 426-8400 F: (216) 426-8411